

SECTION 1: Identification

1.1. Identification

Product form : Mixtures
 Product name : Urethane Catalyst
 Product code : DCUC-2110

1.2. Recommended use and restrictions on use

No additional information available

1.3. Supplier

Uni-Flow Speciality Coatings

T 502-548-7035

1.4. Emergency telephone number

SECTION 2: Hazard(s) identification

2.1. Classification of the substance or mixture

GHS US classification

Flammable liquids Category 3	Flammable liquid and vapour
Acute toxicity (dermal) Category 1	Fatal in contact with skin
Skin corrosion/irritation Category 2	Causes skin irritation
Serious eye damage/eye irritation Category 2	Causes serious eye irritation
Germ cell mutagenicity Category 1B	May cause genetic defects
Carcinogenicity Category 1B	May cause cancer
Reproductive toxicity Category 2	Suspected of damaging fertility or the unborn child
Specific target organ toxicity (single exposure) Category 3	May cause respiratory irritation
Specific target organ toxicity (repeated exposure) Category 1	Causes damage to organs through prolonged or repeated exposure

2.2. GHS Label elements, including precautionary statements

GHS US labeling

Hazard pictograms (GHS US) :



Signal word (GHS US) :

Danger

Hazard statements (GHS US) :

Flammable liquid and vapour
 Fatal in contact with skin
 Causes skin irritation
 Causes serious eye irritation
 May cause respiratory irritation
 May cause genetic defects
 May cause cancer
 Suspected of damaging fertility or the unborn child
 Causes damage to organs through prolonged or repeated exposure

Precautionary statements (GHS US) :

Obtain special instructions before use.
 Do not handle until all safety precautions have been read and understood.
 Keep away from heat/sparks/open flames/hot surfaces. - No smoking.
 Keep container tightly closed.
 Ground/Bond container and receiving equipment
 Use explosion-proof electrical/ventilating/lighting equipment
 Use only non-sparking tools.
 Take precautionary measures against static discharge.
 Do not breathe dust, fume, gas, mist, vapors, spray
 Avoid breathing dust/fume/gas/mist/vapors/spray.
 Do not get in eyes, on skin, or on clothing.
 Wash hands, forearms and face thoroughly after handling.

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Do not eat, drink or smoke when using this product.
Use only outdoors or in a well-ventilated area.
Wear protective gloves/protective clothing/eye protection/face protection.
If on skin: Wash with plenty of water
If on skin (or hair): Take off immediately all contaminated clothing. Rinse skin with water/shower
If inhaled: Remove person to fresh air and keep comfortable for breathing
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
If exposed or concerned: Get medical advice/attention.
Immediately call a poison center or doctor
Call a poison center or doctor if you feel unwell
Get medical advice/attention if you feel unwell.
Specific treatment (see supplemental first aid instruction on this label)
Specific treatment (see supplemental first aid instruction on this label)
If skin irritation occurs: Get medical advice/attention.
If eye irritation persists: Get medical advice/attention.
Take off immediately all contaminated clothing and wash it before reuse.
Take off contaminated clothing and wash it before reuse.
In case of fire: Use media other than water to extinguish.
Store in a well-ventilated place. Keep container tightly closed.
Store in a well-ventilated place. Keep cool.
Store locked up.
Dispose of contents/container to hazardous or special waste collection point, in accordance with local, regional, national and/or international regulation

2.3. Other hazards which do not result in classification

No additional information available

2.4. Unknown acute toxicity (GHS US)

Not applicable

SECTION 3: Composition/Information on ingredients

3.1. Substances

Not applicable

3.2. Mixtures

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Name	Product identifier	%	GHS US classification
Solvent naphtha (petroleum), light arom., Low boiling point naphtha - unspecified, [A complex combination of hydrocarbons obtained from distillation of aromatic streams. It consists predominantly of aromatic hydrocarbons having carbon numbers predominantly in the range of C8 through C10 and boiling in the range of approximately 135°C to 210°C (275°F to 410°F).]	(CAS-No.) 64742-95-6	> 55.44	Flam. Liq. 2, H225 Muta. 1B, H340 Carc. 1B, H350 Asp. Tox. 1, H304
Stoddard solvent, Low boiling point naphtha - unspecified, [A colorless, refined petroleum distillate that is free from rancid or objectionable odors and that boils in a range of approximately 148.8°C to 204.4°C. (300°F to 400°F).]	(CAS-No.) 8052-41-3	~ 22.4	Flam. Liq. 3, H226 Muta. 1B, H340 Carc. 1B, H350 STOT RE 1, H372 Asp. Tox. 1, H304
1,2,4-Trimethylbenzene	(CAS-No.) 95-63-6	< 21.76	Flam. Liq. 3, H226 Acute Tox. 4 (Inhalation), H332 Acute Tox. 4 (Inhalation:vapour), H332 Skin Irrit. 2, H315 Eye Irrit. 2, H319 STOT SE 3, H335 Aquatic Chronic 2, H411
Zinc 2-Ethylhexanoate	(CAS-No.) 136-53-8	~ 12.8	Repr. 2, H361
cumene	(CAS-No.) 98-82-8	< 0.748	Flam. Liq. 3, H226 Carc. 1B, H350 STOT SE 3, H335 Asp. Tox. 1, H304 Aquatic Chronic 2, H411
2-(2-butoxyethoxy)ethanol, diethylene glycol monobutyl ether	(CAS-No.) 112-34-5	~ 0.64	Eye Irrit. 2, H319
Test trade	(CAS-No.) 100-41-4	~ 0.224	Flam. Liq. 2, H225 Acute Tox. 4 (Inhalation), H332 Carc. 2, H351 STOT RE 2, H373 Asp. Tox. 1, H304
Napthalene	(CAS-No.) 91-20-3	~ 0.224	Acute Tox. 4 (Oral), H302 Carc. 1B, H350 Aquatic Acute 1, H400 Aquatic Chronic 1, H410

Full text of hazard classes and H-statements : see section 16

SECTION 4: First-aid measures

4.1. Description of first aid measures

- First-aid measures general : Call a physician immediately.
- First-aid measures after inhalation : Remove person to fresh air and keep comfortable for breathing. Call a poison center/doctor/physician if you feel unwell.
- First-aid measures after skin contact : Rinse skin with water/shower. Remove/Take off immediately all contaminated clothing. Call a physician immediately.
- First-aid measures after eye contact : Rinse eyes with water as a precaution.
- First-aid measures after ingestion : Call a poison center/doctor/physician if you feel unwell.

4.2. Most important symptoms and effects (acute and delayed)

- Symptoms/effects after inhalation : May cause respiratory irritation.
- Symptoms/effects after skin contact : Irritation.
- Symptoms/effects after eye contact : Causes serious eye burns. stinging. Causes serious eye irritation.

4.3. Immediate medical attention and special treatment, if necessary

Treat symptomatically.

SECTION 5: Fire-fighting measures

5.1. Suitable (and unsuitable) extinguishing media

- Suitable extinguishing media : Water spray. Dry powder. Foam. Carbon dioxide.

5.2. Specific hazards arising from the chemical

- Fire hazard : Flammable liquid and vapour.
- Reactivity : Flammable liquid and vapour.

5.3. Special protective equipment and precautions for fire-fighters

- Firefighting instructions : Exercise caution when fighting any chemical fire.

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protection during firefighting : Do not attempt to take action without suitable protective equipment. Self-contained breathing apparatus. Complete protective clothing.

SECTION 6: Accidental release measures

6.1. Personal precautions, protective equipment and emergency procedures

6.1.1. For non-emergency personnel

Emergency procedures : No open flames, no sparks, and no smoking. Only qualified personnel equipped with suitable protective equipment may intervene. Do not breathe dust, fume, gas, mist, vapors, spray.

6.1.2. For emergency responders

Protective equipment : Do not attempt to take action without suitable protective equipment. For further information refer to section 8: "Exposure controls/personal protection".

6.2. Environmental precautions

Avoid release to the environment. Notify authorities if product enters sewers or public waters.

6.3. Methods and material for containment and cleaning up

Methods for cleaning up : Take up liquid spill into absorbent material. Notify authorities if product enters sewers or public waters.

Other information : Dispose of materials or solid residues at an authorized site.

6.4. Reference to other sections

For further information refer to section 13.

SECTION 7: Handling and storage

7.1. Precautions for safe handling

Precautions for safe handling : Ensure good ventilation of the work station. Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. Ground/bond container and receiving equipment. Use only non-sparking tools. Take precautionary measures against static discharge. Flammable vapors may accumulate in the container. Use explosion-proof equipment. Wear personal protective equipment. Obtain special instructions before use. Do not handle until all safety precautions have been read and understood. Take all necessary technical measures to avoid or minimize the release of the product on the workplace. Limit quantities of product at the minimum necessary for handling and limit the number of exposed workers. Provide local exhaust or general room ventilation. Floors, walls and other surfaces in the hazard area must be cleaned regularly. Do not breathe dust, fume, gas, mist, vapors, spray. Do not get in eyes, on skin, or on clothing.

Hygiene measures : Separate working clothes from town clothes. Launder separately. Wash contaminated clothing before reuse. Do not eat, drink or smoke when using this product. Always wash hands after handling the product.

7.2. Conditions for safe storage, including any incompatibilities

Technical measures : Ground/bond container and receiving equipment.

Storage conditions : Store in a well-ventilated place. Keep cool. Keep container tightly closed. Store locked up.

SECTION 8: Exposure controls/personal protection

8.1. Control parameters

Urethane Catalyst		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam; nausea; CNS impair
OSHA	OSHA PEL (TWA) (mg/m³)	2900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
solvent naphtha (petroleum), light aromatic (64742-95-6)		
ACGIH	ACGIH TWA (mg/m³)	200 mg/m³
ACGIH	ACGIH TWA (ppm)	200 ppm
OSHA	OSHA PEL (TWA) (ppm)	200
OSHA	OSHA PEL (STEL) (ppm)	500
cumene (98-82-8)		
ACGIH	ACGIH TWA (ppm)	50 ppm (Cumene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

cumene (98-82-8)		
ACGIH	Remark (ACGIH)	Lung cancer; liver and lung dam; A2 (Suspected Human Carcinogen: Human data are accepted as adequate in quality but are conflicting or insufficient to classify the agent as a confirmed human carcinogen; OR, the agent is carcinogenic in experimental animals at dose(s), by route(s) of exposure, at site(s), of histologic type(s), or by mechanism(s) considered relevant to worker exposure. The A2 is used primarily when there is limited evidence or carcinogenicity in humans and sufficient evidence of carcinogenicity in experimental animals with relevance to humans)
OSHA	OSHA PEL (TWA) (mg/m³)	245 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	50 ppm
1,2,4-Trimethylbenzene (95-63-6)		
ACGIH	ACGIH TWA (ppm)	25 ppm (Trimethyl benzene (mixed isomers); USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
Zinc 2-Ethylhexanoate (136-53-8)		
Not applicable		
Mineral Spirits (Stoddard Solvent) (8052-41-3)		
ACGIH	ACGIH TWA (ppm)	100 ppm
ACGIH	Remark (ACGIH)	Eye, skin, & kidney dam; nausea; CNS impair
OSHA	OSHA PEL (TWA) (mg/m³)	2900 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	500 ppm
Ethanol, 2-(2-butoxyethoxy)- (112-34-5)		
ACGIH	ACGIH TWA (ppm)	10 ppm
ethylbenzene (100-41-4)		
ACGIH	ACGIH TWA (ppm)	20 ppm (Ethyl benzene; USA; Time-weighted average exposure limit 8 h; TLV - Adopted Value)
ACGIH	Remark (ACGIH)	URT irr; kidney dam (nephropathy)
OSHA	OSHA PEL (TWA) (mg/m³)	435 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	100 ppm
Napthalene (91-20-3)		
ACGIH	ACGIH TWA (ppm)	10 ppm
ACGIH	Remark (ACGIH)	Hematologic eff; URT & eye irr; Skin; A3 (Confirmed Animal Carcinogen with Unknown Relevance to Humans: The agent is carcinogenic in experimental animals at a relatively high dose, by route(s) of administration, at site(s), of histologic type(s), or by mechanism(s) that may not be relevant to worker exposure. Available epidemiologic studies do not confirm an increased risk of cancer in exposed humans. Available evidence does not suggest that the agent is likely to cause cancer in humans except under uncommon or unlikely routes or levels of exposure)
OSHA	OSHA PEL (TWA) (mg/m³)	50 mg/m³
OSHA	OSHA PEL (TWA) (ppm)	10 ppm

8.2. Appropriate engineering controls

Appropriate engineering controls : Ensure good ventilation of the work station.
 Environmental exposure controls : Avoid release to the environment.

8.3. Individual protection measures/Personal protective equipment

Hand protection:

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Protective gloves

Eye protection:

Safety glasses

Skin and body protection:

Wear suitable protective clothing

Respiratory protection:

Wear respiratory protection.

SECTION 9: Physical and chemical properties

9.1. Information on basic physical and chemical properties

Physical state	: Liquid
Appearance	: Colorless to pale yellow liquid.
Color	: Colourless to light yellow
Odor	: There may be no odour warning properties, odour is subjective and inadequate to warn of overexposure. Mixture contains one or more component(s) which have the following odour(s): Petroleum-like odour Mild odour Sweet odour Aromatic odour Tar odour No data available on odour Irritating/pungent odour
Odor threshold	: No data available
pH	: No data available
Melting point	: Not applicable
Freezing point	: No data available
Boiling point	: 281 - 283 °F
Flash point	: 80 °F TCC
Relative evaporation rate (butyl acetate=1)	: 0.8
Flammability (solid, gas)	: Not applicable.
Vapor pressure	: 7.6 mm Hg @20 C
Relative vapor density at 20 °C	: No data available
Relative density	: 0.88
Specific gravity / density	: 0.88 g/cm³
Solubility	: Insoluble in water.
Log Pow	: No data available
Auto-ignition temperature	: No data available
Decomposition temperature	: No data available
Viscosity, kinematic	: No data available
Viscosity, dynamic	: No data available
Explosion limits	: No data available
Explosive properties	: No data available
Oxidizing properties	: No data available

9.2. Other information

No additional information available

SECTION 10: Stability and reactivity

10.1. Reactivity

Flammable liquid and vapour.

10.2. Chemical stability

Stable under normal conditions.

10.3. Possibility of hazardous reactions

No dangerous reactions known under normal conditions of use.

10.4. Conditions to avoid

Avoid contact with hot surfaces. Heat. No flames, no sparks. Eliminate all sources of ignition.

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

10.5. Incompatible materials

No additional information available

10.6. Hazardous decomposition products

Under normal conditions of storage and use, hazardous decomposition products should not be produced.

SECTION 11: Toxicological information

11.1. Information on toxicological effects

Acute toxicity : Dermal: Fatal in contact with skin.

Urethane Catalyst	
LD50 oral rat	4000 mg/kg
LD50 dermal rabbit	14100 µg/kg
LC50 inhalation rat (ppm)	4550 ppm/4h
ATE US (oral)	4000.000 mg/kg body weight
ATE US (dermal)	14.100 mg/kg body weight
ATE US (gases)	4550.000 ppmV/4h
solvent naphtha (petroleum), light aromatic (64742-95-6)	
LD50 oral rat	3492 mg/kg
LD50 dermal rabbit	> 3160 mg/kg
LC50 inhalation rat (ppm)	> 6193 ppm/4h
ATE US (oral)	3492.000 mg/kg body weight
cumene (98-82-8)	
LD50 oral rat	> 2000 mg/kg (Rat; Other; Literature study; 4000 mg/kg bodyweight; Rat; Other; Inconclusive, insufficient data)
LD50 dermal rabbit	10578 mg/kg (Rabbit; Literature study; Other)
LC50 inhalation rat (mg/l)	40 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	8000 ppm/4h (Rat; Literature study)
ATE US (dermal)	10578.000 mg/kg body weight
ATE US (gases)	8000.000 ppmV/4h
ATE US (vapors)	40.000 mg/l/4h
ATE US (dust, mist)	40.000 mg/l/4h
1,2,4-Trimethylbenzene (95-63-6)	
LD50 oral rat	> 5000 mg/kg (Rat; Equivalent or similar to OECD 401; Literature; 6000 mg/kg bodyweight; Rat; Experimental value)
LD50 dermal rat	> 3440 mg/kg (Rat; Read-across; OECD 402: Acute Dermal Toxicity)
LC50 inhalation rat (mg/l)	18 mg/l/4h (Rat)
ATE US (gases)	4500.000 ppmV/4h
ATE US (vapors)	18.000 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h
Ethanol, 2-(2-butoxyethoxy)- (112-34-5)	
LD50 dermal rabbit	2764 mg/kg body weight (Equivalent or similar to OECD 402, Rabbit, Male, Experimental value)
ATE US (oral)	2410.000 mg/kg body weight
ATE US (dermal)	2764.000 mg/kg body weight
ethylbenzene (100-41-4)	
LD50 oral rat	3500 mg/kg (Rat; Other; Experimental value)
LD50 dermal rabbit	15415 mg/kg (Rabbit; Literature study; Other; 15432 mg/kg; Rabbit; Experimental value)
LC50 inhalation rat (mg/l)	17.8 mg/l/4h (Rat; Literature study)
LC50 inhalation rat (ppm)	4000 ppm/4h (Rat; Literature study)
ATE US (oral)	3500.000 mg/kg body weight
ATE US (dermal)	15415.000 mg/kg body weight
ATE US (gases)	4000.000 ppmV/4h
ATE US (vapors)	17.800 mg/l/4h
ATE US (dust, mist)	1.500 mg/l/4h

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Naphthalene (91-20-3)	
LD50 dermal rat	> 2500 mg/kg (Rat)
ATE US (oral)	500.000 mg/kg body weight

Skin corrosion/irritation	: Causes skin irritation.
Serious eye damage/irritation	: Causes serious eye irritation.
Respiratory or skin sensitization	: Not classified
Germ cell mutagenicity	: May cause genetic defects.
Carcinogenicity	: May cause cancer.

cumene (98-82-8)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

ethylbenzene (100-41-4)	
IARC group	2B - Possibly carcinogenic to humans

Naphthalene (91-20-3)	
IARC group	2B - Possibly carcinogenic to humans
National Toxicity Program (NTP) Status	3 - Reasonably anticipated to be Human Carcinogen

Reproductive toxicity	: Suspected of damaging fertility or the unborn child.
STOT-single exposure	: May cause respiratory irritation.

Urethane Catalyst	
Target organ(s)	respiratory system

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Target organ(s)	liver kidneys central nervous system

cumene (98-82-8)	
Target organ(s)	liver kidneys central nervous system

STOT-repeated exposure	: Causes damage to organs through prolonged or repeated exposure.
------------------------	---

Aspiration hazard	: Not classified
Symptoms/effects after inhalation	: May cause respiratory irritation.
Symptoms/effects after skin contact	: Irritation.
Symptoms/effects after eye contact	: Causes serious eye burns. stinging. Causes serious eye irritation.

SECTION 12: Ecological information

12.1. Toxicity

Ecology - general	: The product is not considered harmful to aquatic organisms or to cause long-term adverse effects in the environment.
-------------------	--

cumene (98-82-8)	
EC50 Daphnia 1	2.14 mg/l (EC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)

1,2,4-Trimethylbenzene (95-63-6)	
LC50 fish 1	7.72 mg/l (LC50; 96 h; Pimephales promelas; Flow-through system; Fresh water)
EC50 Daphnia 1	3.6 mg/l (LC50; OECD 202: Daphnia sp. Acute Immobilisation Test; 48 h; Daphnia magna; Static system; Fresh water; Experimental value)
Threshold limit algae 2	2.356 mg/l (EC50; ECOSAR; 96 h; Algae; Fresh water)

Ethanol, 2-(2-butoxyethoxy)- (112-34-5)	
LC50 fish 1	1300 mg/l (Equivalent or similar to OECD 203, 96 h, Lepomis macrochirus, Static system, Fresh water, Experimental value)

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Ethanol, 2-(2-butoxyethoxy)- (112-34-5)	
EC50 Daphnia 1	4950 mg/l (Equivalent or similar to OECD 202, 48 h, Daphnia magna, Static system, Fresh water, Experimental value)
ethylbenzene (100-41-4)	
LC50 fish 2	4.2 mg/l (LC50; OECD 203: Fish, Acute Toxicity Test; 96 h; Salmo gairdneri; Semi-static system; Fresh water; Experimental value)
Napthalene (91-20-3)	
LC50 fish 1	0.11 mg/l (96 h, Oncorhynchus mykiss, Literature study)
EC50 Daphnia 1	2.16 mg/l (48 h, Daphnia magna, Literature study)

12.2. Persistence and degradability

cumene (98-82-8)	
Persistence and degradability	Inherently biodegradable. Not readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.28 g O ₂ /g substance
Chemical oxygen demand (COD)	2.42 g O ₂ /g substance
ThOD	3.2 g O ₂ /g substance
BOD (% of ThOD)	0.4
1,2,4-Trimethylbenzene (95-63-6)	
Persistence and degradability	Not readily biodegradable in water. Forming sediments in water. Biodegradable in the soil. Adsorbs into the soil. Low potential for mobility in soil. Photodegradation in the air.
Chemical oxygen demand (COD)	0.44 g O ₂ /g substance

Ethanol, 2-(2-butoxyethoxy)- (112-34-5)	
Persistence and degradability	Readily biodegradable in water.
ethylbenzene (100-41-4)	
Persistence and degradability	Readily biodegradable in water. Biodegradable in the soil. Low potential for adsorption in soil.
Biochemical oxygen demand (BOD)	1.44 g O ₂ /g substance (20d.)
Chemical oxygen demand (COD)	2.1 g O ₂ /g substance
ThOD	3.17 g O ₂ /g substance
BOD (% of ThOD)	45.4 (20 days)
Napthalene (91-20-3)	
Persistence and degradability	Biodegradable in the soil. Readily biodegradable in water.
Biochemical oxygen demand (BOD)	0 g O ₂ /g substance
Chemical oxygen demand (COD)	0.22 g O ₂ /g substance
ThOD	2.99 g O ₂ /g substance

12.3. Bioaccumulative potential

solvent naphtha (petroleum), light aromatic (64742-95-6)	
Log Pow	2.1 - 6
cumene (98-82-8)	
BCF fish 1	35.5 (BCF)
BCF other aquatic organisms 1	94.69 (BCF; BCFBAF v3.00)
Log Pow	3.66 (Experimental value; 3.55; Experimental value; OECD 107: Partition Coefficient (n-octanol/water): Shake Flask Method; 23 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
1,2,4-Trimethylbenzene (95-63-6)	
BCF fish 1	31 - 275 (BCF; Other; 8 weeks; Cyprinus carpio)
Log Pow	3.63 - 4.09 (Experimental value)
Bioaccumulative potential	Potential for bioaccumulation (4 ≥ Log Kow ≤ 5).
Mineral Spirits (Stoddard Solvent) (8052-41-3)	
Log Pow	3.16 - 7.06
Ethanol, 2-(2-butoxyethoxy)- (112-34-5)	
Log Pow	1 (Experimental value, Equivalent or similar to OECD 107, 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (Log Kow < 4).

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylbenzene (100-41-4)	
BCF fish 1	1 (BCF; Other; 6 weeks; Oncorhynchus kisutch; Flow-through system; Salt water; Literature study)
BCF fish 2	15 - 79 (BCF)
BCF other aquatic organisms 1	4.68 (BCF)
Log Pow	3.15 (Experimental value; 3.6; Experimental value; EU Method A.8: Partition Coefficient; 20 °C)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).
Napthalene (91-20-3)	
BCF fish 1	23 - 168 (8 week(s), Cyprinus carpio, Literature study)
Log Pow	3.3 (Experimental value)
Bioaccumulative potential	Low potential for bioaccumulation (BCF < 500).

12.4. Mobility in soil

cumene (98-82-8)	
Log Koc	Koc,884; Calculated value; log Koc; 2.946; Calculated value
1,2,4-Trimethylbenzene (95-63-6)	
Surface tension	0.029 N/m
Log Koc	log Koc,3.04; Calculated value
Ecology - soil	May be harmful to plant growth, blooming and fruit formation.
Mineral Spirits (Stoddard Solvent) (8052-41-3)	
Log Koc	2.85 - 6.74 (log Koc)
Ethanol, 2-(2-butoxyethoxy)- (112-34-5)	
Surface tension	27 mN/m (25 °C, 0.00212 mol/g)
Ecology - soil	Low potential for adsorption in soil.
ethylbenzene (100-41-4)	
Surface tension	0.029 N/m
Log Koc	log Koc,PCKOCWIN v1.66; 2.71; Calculated value; Koc; PCKOCWIN v1.66; 517.8; Calculated value
Napthalene (91-20-3)	
Surface tension	0.03 N/m (100 °C)
Ecology - soil	Adsorbs into the soil.

12.5. Other adverse effects

Effect on the global warming	: No known effects from this product.
GWPmix comment	: No known effects from this product.

SECTION 13: Disposal considerations

13.1. Disposal methods

Waste treatment methods	: Dispose of contents/container in accordance with licensed collector's sorting instructions.
Additional information	: Flammable vapors may accumulate in the container.

SECTION 14: Transport information

Department of Transportation (DOT)

In accordance with DOT

Transport document description	: UN1263 Paint, 3, III
UN-No.(DOT)	: UN1263
Proper Shipping Name (DOT)	: Paint
Class (DOT)	: 3 - Class 3 - Flammable and combustible liquid 49 CFR 173.120
Packing group (DOT)	: III - Minor Danger

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Hazard labels (DOT) : 3 - Flammable liquid



DOT Packaging Non Bulk (49 CFR 173.xxx) : 173

DOT Packaging Bulk (49 CFR 173.xxx) : 242

DOT Special Provisions (49 CFR 172.102) : B1 - If the material has a flash point at or above 38 C (100 F) and below 93 C (200 F), then the bulk packaging requirements of 173.241 of this subchapter are applicable. If the material has a flash point of less than 38 C (100 F), then the bulk packaging requirements of 173.242 of this subchapter are applicable.

B52 - Notwithstanding the provisions of 173.24b of this subchapter, non-reclosing pressure relief devices are authorized on DOT 57 portable tanks.

IB3 - Authorized IBCs: Metal (31A, 31B and 31N); Rigid plastics (31H1 and 31H2); Composite (31HZ1 and 31HA2, 31HB2, 31HN2, 31HD2 and 31HH2). Additional Requirement: Only liquids with a vapor pressure less than or equal to 110 kPa at 50 C (1.1 bar at 122 F), or 130 kPa at 55 C (1.3 bar at 131 F) are authorized, except for UN2672 (also see Special Provision IP8 in Table 2 for UN2672).

T2 - 1.5 178.274(d)(2) Normal..... 178.275(d)(3)

TP1 - The maximum degree of filling must not exceed the degree of filling determined by the following: Degree of filling = $97 / 1 + a (tr - tf)$ Where: tr is the maximum mean bulk temperature during transport, and tf is the temperature in degrees celsius of the liquid during filling.

TP29 - A portable tank having a minimum test pressure of 1.5 bar (150.0 kPa) may be used provided the calculated test pressure is 1.5 bar or less based on the MAWP of the hazardous materials, as defined in 178.275 of this subchapter, where the test pressure is 1.5 times the MAWP.

DOT Packaging Exceptions (49 CFR 173.xxx) : 150

DOT Quantity Limitations Passenger aircraft/rail (49 CFR 173.27) : 60 L

DOT Quantity Limitations Cargo aircraft only (49 CFR 175.75) : 220 L

DOT Vessel Stowage Location : A - The material may be stowed "on deck" or "under deck" on a cargo vessel and on a passenger vessel.

Emergency Response Guide (ERG) Number : 128

Other information : No supplementary information available.

Transportation of Dangerous Goods

Not applicable

Transport by sea

Transport document description (IMDG) : UN 1263 PAINT, 3, III

UN-No. (IMDG) : 1263

Proper Shipping Name (IMDG) : PAINT

Class (IMDG) : 3 - Flammable liquids

Packing group (IMDG) : III - substances presenting low danger

Limited quantities (IMDG) : 5 L

Air transport

Transport document description (IATA) : UN 1263 Paint, 3, III

UN-No. (IATA) : 1263

Proper Shipping Name (IATA) : Paint

Class (IATA) : 3 - Flammable Liquids

Packing group (IATA) : III - Minor Danger

SECTION 15: Regulatory information

15.1. US Federal regulations

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

cumene (98-82-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 5000 lb

1,2,4-Trimethylbenzene (95-63-6)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

Zinc 2-Ethylhexanoate (136-53-8)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Mineral Spirits (Stoddard Solvent) (8052-41-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

Ethanol, 2-(2-butoxyethoxy)- (112-34-5)

Listed on the United States TSCA (Toxic Substances Control Act) inventory

ethylbenzene (100-41-4)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 1000 lb

Napthalene (91-20-3)

Listed on the United States TSCA (Toxic Substances Control Act) inventory
Subject to reporting requirements of United States SARA Section 313

CERCLA RQ 100 lb

15.2. International regulations

CANADA

solvent naphtha (petroleum), light aromatic (64742-95-6)

Listed on the Canadian DSL (Domestic Substances List)

cumene (98-82-8)

Listed on the Canadian DSL (Domestic Substances List)

1,2,4-Trimethylbenzene (95-63-6)

Listed on the Canadian DSL (Domestic Substances List)

Zinc 2-Ethylhexanoate (136-53-8)

Listed on the Canadian DSL (Domestic Substances List)

Mineral Spirits (Stoddard Solvent) (8052-41-3)

Listed on the Canadian DSL (Domestic Substances List)

Ethanol, 2-(2-butoxyethoxy)- (112-34-5)

Listed on the Canadian DSL (Domestic Substances List)

ethylbenzene (100-41-4)

Listed on the Canadian DSL (Domestic Substances List)

Napthalene (91-20-3)

Listed on the Canadian DSL (Domestic Substances List)

EU-Regulations

No additional information available

National regulations

cumene (98-82-8)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

ethylbenzene (100-41-4)

Listed on IARC (International Agency for Research on Cancer)

Napthalene (91-20-3)

Listed on IARC (International Agency for Research on Cancer)
Listed as carcinogen on NTP (National Toxicology Program)

15.3. US State regulations

cumene (98-82-8)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

ethylbenzene (100-41-4)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	54

Napthalene (91-20-3)

U.S. - California - Proposition 65 - Carcinogens List	U.S. - California - Proposition 65 - Developmental Toxicity	U.S. - California - Proposition 65 - Reproductive Toxicity - Female	U.S. - California - Proposition 65 - Reproductive Toxicity - Male	No significant risk level (NSRL)
Yes	No	No	No	

cumene (98-82-8)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

1,2,4-Trimethylbenzene (95-63-6)

U.S. - New Jersey - Right to Know Hazardous Substance List

Mineral Spirits (Stoddard Solvent) (8052-41-3)

U.S. - New Jersey - Right to Know Hazardous Substance List

ethylbenzene (100-41-4)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

Napthalene (91-20-3)

U.S. - New Jersey - Right to Know Hazardous Substance List
U.S. - Pennsylvania - RTK (Right to Know) List

SECTION 16: Other information

Revision date : 04/10/2018

Urethane Catalyst

Safety Data Sheet

according to Federal Register / Vol. 77, No. 58 / Monday, March 26, 2012 / Rules and Regulations

Full text of H-phrases:

H225	Highly flammable liquid and vapour
H226	Flammable liquid and vapour
H302	Harmful if swallowed
H304	May be fatal if swallowed and enters airways
H310	Fatal in contact with skin
H315	Causes skin irritation
H319	Causes serious eye irritation
H332	Harmful if inhaled
H335	May cause respiratory irritation
H340	May cause genetic defects
H350	May cause cancer
H351	Suspected of causing cancer
H361	Suspected of damaging fertility or the unborn child
H372	Causes damage to organs through prolonged or repeated exposure
H373	May cause damage to organs through prolonged or repeated exposure
H400	Very toxic to aquatic life
H410	Very toxic to aquatic life with long lasting effects
H411	Toxic to aquatic life with long lasting effects

SDS US (GHS HazCom 2012)

This information is based on our current knowledge and is intended to describe the product for the purposes of health, safety and environmental requirements only. It should not therefore be construed as guaranteeing any specific property of the product.